



#### CONCRETE

- ① ODOT ITEM 452 NONREINFORCED OR ODOT ITEM 451 REINFORCED CONCRETE PAVEMENT (8" THICK)

#### ASPHALT

- ① ODOT ITEM 448 - ASPHALT CONCRETE (1-1/2" THICK)  
PAVEMENT SURFACE COURSE
- ② ODOT ITEM 301 - (8" THICK)  
PAVEMENT BASE COURSE
- ③ ALL PAVEMENT TRENCH SECTIONS REQUIRE ODOT 304 CRUSHED AGGREGATE
- ④ BACKFILL, ODOT 304 LIMESTONE REQUIRED UNDER PAVEMENTS, DRIVEWAYS, ETC. IN LAYERS NOT EXCEEDING 8" LOOSE DEPTH AND COMPACTED BY MECHANICAL DEVICES TO NOT LESS THAN 98% OF STANDARD DENSITY.
- ⑤ BACKFILL OUTSIDE INFLUENCE LINE, CONFORMING TO ODOT 203, EXCAVATED EARTH FREE FROM DEBRIS, COMPACTED TO AT LEAST DENSITY OF SURROUNDING GROUND.

#### NOTES:

1. PAVEMENT REPAIR AND BACKFILL REQUIREMENTS SUBJECT TO ROADWAY JURISDICTIONAL REQUIREMENTS.